



TIANYI CABLE

Tel:+86 571 23619066

E-mail:sales@wanmatianyi.com

Homepage: www.wanmatianyi.com

RG59 TRI

75 Ohm Coaxial Cable



Physical Specifications

| Item | Material | Diameter |
|-----------------|---------------------|----------|
| Inner Conductor | CCS/CU | 0.81mm |
| Dielectric | Foamed Polyethylene | 3.66mm |
| First Shield | Aluminum Foil | 3.84mm |
| Second Shield | Aluminum Braid | 4.47mm |
| Third Shield | Aluminum Foil | 4.57mm |
| Jacket | PVC | 6.10mm |

Electrical specifications

| | | | |
|---------------------------------|-------|------|--|
| Impedance | 75±3Ω | | |
| Nominal Velocity of propagation | 85% | | |
| Structural Return Loss ≥ | VHF | 22dB | |
| | UHF | 20dB | |

Package

Carton Nominal packaging 6×100m or 3×200m/carton. According to customers' requirements.

Wooden Reel Nominal packaging 1000ft/reel. According to customers' requirements.

Attenuation @ 68°F (20°C)

| | |
|---------|--------------|
| 5MHz | 2.91dB/100m |
| 55MHz | 6.73dB/100m |
| 83MHz | 8.04dB/100m |
| 187MHz | 11.81dB/100m |
| 211MHz | 12.47dB/100m |
| 250MHz | 13.45dB/100m |
| 300MHz | 14.60dB/100m |
| 350MHz | 15.75dB/100m |
| 400MHz | 16.73dB/100m |
| 450MHz | 17.72dB/100m |
| 500MHz | 18.70dB/100m |
| 550MHz | 19.52dB/100m |
| 600MHz | 20.34dB/100m |
| 750MHz | 22.87dB/100m |
| 865MHz | 24.67dB/100m |
| 1000MHz | 26.64dB/100m |

